



Halogen reflector

13938XHP 50W GX5.3 22.8V 1CT/24

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.


Product data

General Information		Mechanical and Housing	
Cap-Base	GX5.3	Bulb Material	Quartz-UV Open
Operating Position	UNIVERSAL [Any or Universal (U)]	Reflector Finish	Smooth
Life to 50% Failures (Nom)	750 hour(s)	Bulb Shape	R50
		Net Weight (Piece)	27.000 g
Light Technical		Approval and Application	
Correlated Color Temperature (Nom)	3200 K	CE mark	Yes
Color rendering index (CRI)	100		
Operating and Electrical		Product Data	
Power Consumption	50 W	Order product name	13938XHP 50W GX5.3 22.8V 1CT/24
Voltage (Nom)	22.8 V	Full product name	13938XHP 50W GX5.3 22.8V 1CT/24
		Full product code	871869669019200
Controls and Dimming		Order code	924059828302
Dimmable	Yes	Material Nr. (12NC)	924059828302
		Numerator - Quantity Per Pack	1

Halogen reflector

EAN/UPC - Product/Case	8718696690192
Numerator - Packs per outer box	24
EAN/UPC - Case	8718696690208

Dimensional drawing



Product	D (max)	C (max)
13938XHP 50W GX5.3 22.8V 1CT/24	50 mm	45 mm

