



CorePro LED PLC

CorePro LED PLC CorePro LED PLC 4.5W 840 2P G24d-1

Philips CorePro LED PLC is the ideal uplampping solution for downlights in a wide range of general lighting applications. It integrates a LED light source into a traditional fluorescent form factor to offer superb energy savings over a lifetime that's twice as long as fluorescent alternatives.

Product data

General Information		Power Factor (Nom)	0.9
Cap-Base	G24D-1 [G24d-1]	Voltage (Nom)	220-240 V
Nominal Lifetime (Nom)	30000 h	Temperature	
Switching Cycle	50000X	T-Ambient (Max)	35 °C
B50L70	30000 h	T-Ambient (Min)	-20 °C
Light Technical		T-Storage (Max)	65 °C
Color Code	840 [CCT of 4000K]	T-Storage (Min)	-40 °C
Luminous Flux (Nom)	500 lm	T-Case Maximum (Nom)	60 °C
Luminous Flux (Rated) (Nom)	500 lm	Controls and Dimming	
Correlated Color Temperature (Nom)	4000 K	Dimmable	No
Color Consistency	<6	Mechanical and Housing	
Color Rendering Index (Nom)	83	Product Length	100 mm
LLMF At End Of Nominal Lifetime (Nom)	70 %	Approval and Application	
Operating and Electrical		Energy Saving Product	Yes
Input Frequency	50 to 60 Hz	Energy Efficiency Label (EEL)	A++
Power (Rated) (Nom)	4.5 W	Approval Marks	TUV CE marking RoHS compliance KEMA Keur certificate
Lamp Current (Max)	25 mA		
Lamp Current (Min)	20 mA		
Starting Time (Nom)	0.5 s		
Warm Up Time to 60% Light (Nom)	0.5 s		

CorePro LED PLC


Energy Consumption kWh/1000 h	5 kWh
Product Data	
Full product code	871869670661900
Order product name	CorePro LED PLC CorePro LED PLC 4.5W 840 2P G24d-1
EAN/UPC - Product	8718696706619

Order code	929001350802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001350802
Net Weight (Piece)	0.070 kg

Warnings and Safety

- NOTES: The overall energy efficiency and light distribution of any installation that uses these lamps are determined by the design of the installation.


Dimensional drawing




PLED PLC 230V 5W 500lm 4000K G24D-1 ND

Product	D1	D2	A1	A2	A3
CorePro LED PLC 4.5W 840 2P G24d-1	24.3 mm	28.4 mm	95.8 mm	115 mm	137.6 mm

Photometric data




General Uniform Lighting
1 - PLED-OW ASSEMBLED LED TUBES
Page 17



LEDtube 100mm 5W G24D-1 840 500lm


CorePro LED PLC

Photometric data




LEDtube 100mm 5W G24D-1

Lifetime



LEDtube 100mm 5W G24D-1



LEDtube 100mm 5W G24D-1

